

packaging paper & board converting

bags & sacks

water-based **adhesives**

for **bags and sacks applications**

Experience performance from our **water-based adhesives** for **bags and sacks applications**



Both for the production of single- and multiwall paper bags, we offer a full range of adhesive products. Highly viscous, paste adhesives for bottom-gluing, nozzle-applied side seam adhesives, but also adhesives for window gluing and handle or liner attachment are part of our portfolio.



		Product	Туре	Colour	Solid Content* (%)	Viscosity** @20°C (mPa.s)	Application	Description
Multi - Wall Bags	Paper to Film	Enziflex PC 19	Acrylic	White	67	1050	Segment	Acrylate-based Pressure Sensitive Adhesive for glueing (corona) treated Polyethylene/high density Polyethylene.
Single - Wall Bags	Side Seam	Multicollix P 104 B	PVAc / Starch	White	22	3500	Nozzle / Wheel	Starch-based side seam adhesive for untreated or slightly treated paper.
		Latyl PZ 53	PVAc	White	50	2400	Nozzle / Wheel	Homopolymer-based adhesive for the top seam of flour bags or side seam of single wall bags, high setting speed.
		Enziflex K 6750 V40	PVAc	White	32	4000	Nozzle / Roller	Homopolymer-based adhesive for the side seam of single wall bags, slow setting time. Suitable for multi-beam nozzles.
		Enziflex K 6511	VAE-Acryl	White	55	2000	Segments	Terpolymer-based adhesive for gluing PVC, PS, OPP foils on paper bags.
	Bottom Paste	Multicollix P 104 N3	Starch	Off-White	20	47000***	Segments	Starch-based bottom paste adhesive for untreated paper.
		Latyl Z 50	Starch	White	25	44000***	Segments	Starch-based bottom paste adhesive for treated paper.
		Enziflex K 6511 BP	VAE-Acryl	White	58	25000***	Segments	Terpolymer-based bottom paste adhesive specially developed for single-wall bags with window / coated, lacquered and paraffin coated paper.
Paraffin Bags	Side Seam	Latyl Z 112 L	PVAc	White	28	5500	Nozzle / Wheel	Homopolymer-based side seam adhesive for the parrafin coated single wall bags.
	Bottom Paste	Latyl Z 106 B	PVAc	White	25	50000***	Segments	Homopolymer-based bottom paste adhesive for the parrafin coated single wall bags.

* Dry solids measured according to ISO 3251, for detailed information refer to the TDS.
** Viscosity measured according to ISO 2555 ("Brookfield"), for detailed information refer to the TDS.

*** Viscosity measured according to ASTM D2556, for detailed information refer to the TDS.

Paramelt B.V.

t +31 72 57 50 600

Costerstraat 18 1704 RJ Heerhugowaard The Netherlands

waxes adhesives coatings

Paramelt Veendam B.V.

Adriaan Tripweg 25 9641 KN Veendam The Netherlands t +31 59 86 62 500

Enziflex[™] and Latyl[™] are trademarks of Paramelt Information and details given in this document, particularly any recommendations for application and use of our products are based on careful laboratory tests and prevailing practical experience and are believed to be correct at time of publication. For more information: paramelt.com/disclaimer



www.paramelt.com