



packaging | labeling

V_2026_04

Labeling adhesives

For glass and plastic bottles

Formulating solutions. Together.

We offer a comprehensive range of machine-applied labeling adhesives for all aspects of your can and bottle labeling operations. The range consists of synthetic, hybrid, casein and hot melt adhesives, covering both glass bottle labeling as well as plastic bottles for carbonated drinks.

	Product	Container	Type	Bottle °C	CWR*	IWR**	Product in brief
Water-based adhesives	Multicollac SEF 200	Glass	Casein	> 0°C	+++	+	Good CWR and IWR.
	Multicollac F 99	Glass	Casein	> 6°C	++		Standard Casein grade.
	Latyl ES 26	Glass	Hybrid	> 8°C	++		Hybrid grade for moist and cold application.
	Latyl ES 77	Glass	Hybrid	> 8°C	++		Cost effective versatile hybrid grade.
	Latyl ES 550	Glass	Synthetic	> 6°C	+++	+++	Very fast setting adhesive with good IWR for returnable bottles.
	Latyl ES 500	Glass	Synthetic	> 6°C	+++	+	Fast setting adhesive with optimized machine properties for returnable bottles.
	Latyl ES 303	Glass	Synthetic	> 8°C	+++	++	Very fast setting adhesive with excellent IWR for non-returnable bottles.
	Latyl ES 240	Glass	Synthetic	> 6°C	++		Cost effective versatile synthetic grade for returnable bottles.
	Latyl ES 100	Glass	Synthetic	> 10°C	+		Versatile synthetic grade.
	Latyl E 256	Glass	Starch	> 15°C			Standard starch grade for glass applications with speed ≤15.000.
	Latyl E 395	PET, PVC	Hybrid	> 8°C	++		One way bottles, high speed lines.

	Product	Container	Type	Application by	Label	CO ₂	Product in brief
Hot melt adhesives	Plastoflex 9160	PET, PVC, glass	Semi PSA	Roller & nozzle	paper	N	For horizontal and vertical labeling. Runs well on low speed applications e.g. tax stamps as well as high speed applications for labeling of non-carbonated bottles.
	Plastoflex 9165	PET	PSA	Roller & nozzle	OPP, paper	Y	For vertical PET bottle labeling on medium to high speed lines. Works with paper and plastic pre-cut labels.
	Plastoflex 9605	PET	PSA	Roller & nozzle	OPP	Y, high	For vertical PET bottle labeling on high speed machines, roll-fed and pre-cut labels. Suitable for high carbonation levels.

We are Paramelt

When your products depend on the consistent performance of waxes, adhesives, and coatings, reliability becomes essential. Today's manufacturing challenges, from supply chain volatility to increasing regulatory and sustainability demands, require partners who respond with certainty and expertise. Many of the world's most trusted brands rely on Paramelt for dependable quality, secure supply, and deep formulation knowledge in demanding applications. We collaborate closely, support your goals, and help you move forward.

We listen, adapt and deliver!

Paramelt B.V.

Costerstraat 18
1704 RJ Heerhugowaard
The Netherlands
t +31 72 57 50 600

Paramelt Veendam B.V.

Adriaan Tripweg 25
9641 KN Veendam
The Netherlands
t +31 59 86 62 500

Latyl™ and Plastoflex™ are trademarks of Paramelt. Information and details given in this document, particularly any recommendations for application and use of our products are based on careful laboratory tests and prevailing practical experience and are believed to be correct at time of publication. For more information: paramelt.com/disclaimer